


Bluetooth® Passive Infrared Sensor

SPECIFICATION

The ANT-21P-4T-H-BLE-GE uses PIR motion detector architecture and passive infrared (PIR) technology for improved detection coverage for high bay applications.




OVERVIEW

- PIR sensor.
- Daylight Harvesting
- Bluetooth® SIG mesh.
- High-End Trim, Zoning, Continuous Bi-level Dimming.
- LED Motion indicator.
- Mounting height up to 40ft.
- 360° coverage pattern.
- Low Voltage connector.

FEATURES AND BENEFITS


- Bluetooth to 0-10V signal converter, Bluetooth® mesh network.
- Built-in 20mA 0-10V signal output.
- Mesh network, which has a much longer control distance, transmits received signals to neighboring devices.
- All devices on 0-10V line are broadcast controlled by mobile application.
- In typical outdoor environment, the typical range for wireless communication is 164ft(50m).
- Actual range is dependent on field installation.
- Available with magnetic reset(Touch the side part of sensor for 5 seconds) and remote reset (press "RESET"+" ON/OFF" buttons in sequence).
- On-board antenna.



TECHNICAL DATA

Motion Sensor	Passive infrared sensor
Input Power	12-24VDC,>50mA
Control Output	0-10V,max 25mA sinking current
Mounting height	Max 20ft.(6meters)
Detection angle	360°
Operating temperature	-20°C~60°C
IP rating	65
Max Bluetooth Range	164ft(50m)
Warranty	5years

SENSOR COVERAGE



ORDERING INFORMATION

ANT-21P-4T-H-BLE-GE

Bluetooth® Passive Infrared Sensor